



**GENERAL INFO** **SEDIMENT REMOVAL CARTRIDGE**

**Ribbed Sediment Cartridges**

Puretec RB Series cartridges uses grooves to increase surface area for greater dirt-holding capacity. These cartridges reduces dirt, rust, algae and organic matter.

**FEATURES & BENEFITS**

- Graded density ribbed design for longer life
- Available in 5, 25 and 50 microns
- Flow rates up to 166 litres/minute
- Large surface area from ribbed design gives longer service life
- Maximum temperature at 60°C

**MATERIALS OF CONSTRUCTION**

- Filter Media                      Polypropylene
- Temperature Rating            32°F to 140°F (0°C to 60°C)

**HOUSING SPECIFICATIONS AND PERFORMANCE DATA**

Model	Micron Rating	Size	Min/Max Temp	Min/Max Pressure	Min/Max Flow (Lpm)
<b>RB051</b>	5	standard 2.5" x 10"	0 - 60 °C	100-900 kPa	0 - 28
<b>RB251</b>	25	standard 2.5" x 10"	0 - 60 °C	100-900 kPa	0 - 35
<b>RB501</b>	50	standard 2.5" x 10"	0 - 60 °C	100-900 kPa	0 - 38
<b>RB05MP1</b>	5	MaxiPlus™ 4.5" x 10"	0 - 60 °C	100-900 kPa	0 - 76
<b>RB25MP1</b>	25	MaxiPlus™ 4.5" x 10"	0 - 60 °C	100-900 kPa	0 - 85
<b>RB05MP2</b>	5	MaxiPlus™ 4.5" x 20"	0 - 60 °C	100-900 kPa	0 - 156
<b>RB25MP2</b>	25	MaxiPlus™ 4.5" x 20"	0 - 60 °C	100-900 kPa	0 - 166